

A6/V6 Series

Bill Acceptor

- Four-way bill insertion.
- Numerous interfaces available.
- Easy installation and maintenance.
- High acceptance rate up to 96%.
- Auto-calibrating.



ict

A6/V6 Series

Bill Acceptor

A6/V6 Series is a bill acceptor which features not only high-security module with bill box but also outstanding recognition, acceptance rate up to 96% or even greater.

Specifications



Acceptance Rate

96% or greater



Bill Insertion

Four-way



Bill Width Accepted

60~67 mm/ 2.36~2.63 inches



Capacity

Approx. 100 bills (40~ 140)
300 bills (200~ 300)
500 bills (300~ 500)
550 bills (440~ 640)
800 bills (750~ 850)
1000 bills (1000~1140)



Dimension

100 bills:
(W)94 x (D)91 x (H)235.9 mm/
(W)3.70 x (D)3.58 x (H)9.28 inches

300 bills:
(W)94 x (D)115 x (H)235.9 mm/
(W)3.70 x (D)4.53 x (H)9.28 inches

500 bills:
(W)94 x (D)130 x (H)235.9 mm/
(W)3.70 x (D)5.12 x (H)9.28 inches

550 bills:
(W)94 x (D)153 x (H)235.9 mm/
(W)3.70 x (D)6.02 x (H)9.28 inches

800 bills:
(W)94 x (D)190 x (H)235.9 mm/
(W)3.70 x (D)7.48 x (H)9.28 inches

1000 bills:
(W)94 x (D)232 x (H)235.9 mm/
(W)3.70 x (D)9.13 x (H)9.28 inches



Acceptance Speed

Approx. 3 sec. to cashbox



Interface

A6: Standard Pulse, 5V Enable, ICT Protocol,
Single price
V6: MDB



Power Source

A6: 12V DC (11.4~12.6V DC)
117V AC (105.3~128.7V AC)
V6: 24V/34V DC (20V~42.5V DC)



Power Consumption

A6: 12V DC Standby : 0.3A, 4W
Operation: 0.9A, 11W
Maximum: 2.6A, 32W
117V AC Standby : 0.06A, 7W
Operation: 0.112A, 14W
Maximum: 0.4A, 47W
V6: 24V/34V DC Standby : 0.15A, 6W
Operation: 0.4A, 14W
Maximum: 1.35A, 46W



Weight

Approx. 2 kg/ 4.4 lbs



Environmental

Operating Temperature:
0°C/ 32°F ~ 55 °C/ 131°F
Storage Temperature:
-30°C /-22 °F~ 70 °C/ 158°F
Humidity: 30%~85% RH (No Condensation)



Recommended Applications

Indoor Vending, Gaming, Amusement

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw