

CSD Series

Card Dispenser

- Standard type and drop type card dispenser available
- Multi-inteface: Pulse, Hopper, RS232
- 12V and 24V DC power acceptable
- Card capacity of 300 to 600 cards
- Easy card filling



ict

CSD Series

Card Dispenser

CSD is a card vending dispenser with Standard type or Drop type as reliable card dispenser which is able to work steadily and fast approx 1 second per card.

Specifications



Card Dispensing Speed

Approx. 1 sec.



Interface

Hopper
Pulse
RS232



Power Source

12V DC (11.4V~12.6V DC)
24V DC (22.8V~25.2V DC)



Power Consumption

12V DC- Standby : 0.25A, 3W
Operation: 1.25A, 15W
Maximum: 2.5A, 30W
24V DC- Standby : 0.13A, 3.2W
Operation: 0.83A, 20W
Maximum: 1.66A, 40W



Applicable Cards

Material: Plastic, Paper Cards
Size- Thickness: 0.4~1.0mm (Max.)
Width : 58~63 ±0.5mm
Length : 76~90 ±0.5mm



Card Capacity

CSD2300: Approx. 300 cards
CSD2600: Approx. 600 cards
(a card thickness of 0.4mm)



Dispensing Way

Standard Type:
Card will be held in slot when dispensing.

Drop Type:
Card will be dropped out from slot when dispensing.



Dimension

Standard Type
(W)106 x (D)173.7 x (H)327 mm/
(W)4.17 x (D) 6.83 x (H)12.87 inches

Drop Type:
(W)106 x (D)168.7 x (H)180 mm/
(W)4.17 x (D) 6.64 x (H)7.09 inches



Weight

CSD2300: Approx. 2.2kg
CSD2600: Approx. 2.9kg



Environmental

Operating Temperature:
0°C/32°F~50°C/122°F
Storage Temperature:
-30°C/-22°F~70°C/158°F
Humidity: 30%~90RH%
(no condensation)



Recommended Applications

Indoor Gaming
Vending
Kiosk

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw