

CVD Series

Card Dispenser

- Standard type and drop type card dispenser available.
- Low level sensor function(optional).
- Multi-interface: Pulse, Hopper, RS232.
- 12V and 24V DC power acceptable.
- Card capacity of 300 to 1000 cards.
- Easy card filling.



CVD Series

Card Dispenser

CVD series is a card vending dispenser which is base on the design of CVD series. The machine features low level sensor function with Standard type or Drop type as reliable card dispenser which is able to work steadily and fast approx 1 second per card.

Specifications



Card Dispensing Speed

Approx. 1 sec./ Card



Interface

Hopper
Pulse
RS232



Applicable Cards

Material: Plastic, Paper Cards (Opaque)
Size : Thickness 0.2~1.0mm(max.)
Width 53~58 ±0.5mm
Length 76~90 ±0.5mm



Card Capacity

CVD2300 : Approx. 300 cards
CVD21000: Approx.1000 cards
(a card thickness of 0.2mm)



Power Source

12V DC (11.4V~12.6V DC)
24V DC (22.8V~25.2V DC)



Power Consumption

12V DC- Standby : 0.25A, 3W
Operation: 1.25A, 15W
Maximum: 2.5A, 30W
24V DC- Standby : 0.13A, 3.2W
Operation: 0.83A, 20W
Maximum: 1.66A, 40W



Dimension

Standard Type/ Drop Type:

CVD2300 :
(W)100 x (D)166.2 x (H)180.2 mm/
(W)3.94 x (D)6.54 x (H)7.09 inches
CVD21000 :
(W)100 x (D)166.2 x (H)445.2 mm/
(W)3.94 x (D)6.54 x (H)17.53 inches

With Low Level Sensor:

CVD2300:
(W)100 x (D)166.2 x (H)180 mm/
(W)3.94 x (D)6.54 x (H)7.09 inches
CVD21000 :
(W)100 x (D)166.2 x (H)445 mm/
(W)3.94 x (D)6.54 x (H)17.52 inches



Weight

CVD2300 : Approx. 1.9 kg
CVD21000: Approx. 3.2 kg



Environmental

Operating Temperature:
0°C/32°F~50°C/122°F
Storage Temperature:
-30°C/-22°F~70°C/158°F
Humidity: 30%~90RH%(no condensation)



Recommended Applications

Indoor Gaming, Vending, Kiosk



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw