

LX7-A-USD6

LX7-A Option Switch Settings: 1(Pulse/ICT002U/RS232 A0/NISR)

Supported bill USD 1, 5, 10, 20, 50, 100 6bills.

LX7-A dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject USD 1	ON											
★	Accept USD 1	OFF											
★	Reject USD 5		ON										
★	Accept USD 5		OFF										
★	Reject USD 10			ON									
★	Accept USD 10			OFF									
★	Reject USD 20				ON								
★	Accept USD 20				OFF								
★	Reject USD 50 & 100					ON							
★	Accept USD 50 & 100					OFF							
	Auto Detection SEND Signal	(NISR only)				ON							
★	Normal High SEND Signal	(NISR only)				OFF							
	Pulse Mode	Other Mode											
	Harness Disable	BA stops working when fishing				ON							
★	Harness Enable	Normal				OFF							
	Inhibit Active High							ON					
★	Inhibit Active Low							OFF					
★	1 pulse / USD 1								OFF	OFF			
	2 pulses / USD 1								ON	OFF			
	4 pulses / USD 1								OFF	ON			
	20 pulses / USD 1								ON	ON			
★	Pulse Speed	50ms LO / 50ms HI									OFF	OFF	
		60ms LO / 300ms HI									ON	OFF	
		30ms LO / 50ms HI									OFF	ON	
		150ms LO / 150ms HI									ON	ON	

★ Manufacture setting

Note : (1) Default setting.

(2) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

LX7-A-USD6(Pulse/ICT002U/RS232 A0/NISR)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON	OFF	
	NISR Interface		OFF	ON	
	ICT002U Interface		ON	ON	
	RS232 A0 Interface		OFF	OFF	
★	Reserved				ON
					OFF

Currency Assign Data

Interface Bill value	Pulse	RS232 A0	NISR	ICT002U
BV1	USD 1	USD 1	USD 1	USD 1
BV2	USD 5			USD 5
BV3	USD 10	USD 5	USD 5	USD 10
BV4	USD 20	USD 10	USD 10	USD 20
BV5	USD 50	USD 20	USD 20	USD 50
BV6	USD 100	USD 50	USD 50	USD 100
BV7		USD 100	USD 100	

DIP SWITCHES SETTING : 2(ICT002U)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
	NISR Interface		OFF	ON	
★	ICT002U Interface		ON	ON	
	RS232 A0 Interface		OFF	OFF	
★	Reserved				ON
					OFF

DIP SWITCHES SETTING : 2(NISR)

	FUNCTION	SW1	SW2	SW3	SW4
★	Send ERROR CODE	ON			
	No ERROR CODE	OFF			
	Pulse Mode		ON	OFF	
★	NISR Interface		OFF	ON	
	ICT002U Interface		ON	ON	
	RS232 A0 Interface		OFF	OFF	
	Standard Mode				ON
★	Customized Mode				OFF

DIP SWITCHES SETTING : 2(RS232 A0)

	FUNCTION	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Mode		ON	OFF	
	NISR Interface		OFF	ON	
★	RS232 A0 Interface		OFF	OFF	
★	Reserved				ON
					OFF

RS232 A0 INFORMATION

BillType Data	
Code	Denomination
1	USD 1
2	Reserved
3	USD 5
4	USD 10
5	USD 20
6	USD 50
7	USD 100

★ Manufacture setting