

SP1-V/ XBA Combo

Smart Printer for Vending

- Design dedicated for Vending Applications
- Easy Installation and Low Maintenance
- Anti-Pull Paper Mechanism
- Adjustable Paper Length
- Low-paper Alarm Indicator
- Quick, Easy Settings & Upgrade via USB Pen-drive



ict

SP1-V/ XBA Combo

Smart Printer for Vending

SP1-V, a compact-size design, is installed on the vending machine that needs the functionality of output a receipt while the transaction completed. The friendly user interface of built-in print-button and the adjustable paper length function, the user can easy and quick operate SP1-V to increase the efficiency of paper-use and reduce the maintenance cost.

With a DAB (ICT's Data Audit Box) installation, it can satisfy the operator not only the requirements of audit transaction (DAB) but also to print out the receipt/ coupon for the vending machines.

Both coupon and receipt, the format including the logo, text contents and QR/ bar code, etc, can be set-up by the user. The downloadable design that the operator can save or upload the printing format/settings between SP1-V and utility tool via a USB pen-drive would considerable educe the maintenance efforts.

Specifications

 Printing Method Thermal dot-line printing	 Power Source 20VDC~45VDC 24VAC
 Printing Speed 90±5mm/sec	 Power Consumption Standby: 2.4W Operation: 14.4W Maximum: 84W (in case of printing in all gray)
 Paper Size Width: 58±0.5 mm/ 2.28±0.02 inches Outside Diameter: 40±1.0 mm/ 1.57±0.02 inches	 Dimension SP1-V (H)132 x (W)102 x (D)155.3 mm / (H) 5.2 x (W) 4.0 x (D) 6.1 inches Combo (H)302.1 x (W)101.9 x (D)189.5 mm/ (H) 11.9 x (W) 4.01 x (D) 7.46 inches
 Paper-Length Adjustment 70~114 mm/ 2.75~4.48 inches	 Weight SP1-V Approx. 700g / 1.55 lbs(without paper roll) Combo Approx. 2200g / 4.85 lbs
 Resolution 8 dots/ mm	 Environmental Operation Temperature: 0°C/32°F~50°C/122°F Storage Temperature: -20°C/-4°F~60°C/140°F Humidity: 30%~85% (no condensation)
 Character Set 5 Font Sizes (8*13, 16*24, 24*36, 32*48, 48*72)	 Certificate CE, FCC
 Interface DAB (ICT Protocol) Setting/ Download: RS232, USB	 Recommended Applications Vending
 Printer Mode Auto Mode Button Mode	

Specifications are subject to change without prior notice.
All trademarks and copyrights mentioned herein belong to their respective owners.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan
Phone: +886-2-2793-1236
Fax: +886-2-2793-6125
Email: sales@ictgroup.com.tw (Product Information)
fae@ictgroup.com.tw (Technical Service)
Website: www.ictgroup.com.tw