

TAO-A/V I Series

Bill Acceptor

- Secure, lockable, and removable bill box is available for 200, 500 and 1000 bills capacity.
- Four way bill insertion acceptance.
- Auto-calibrating.



ict

TAO-A/V I Series

Bill Acceptor

TAO-A/V I series is a bill acceptor which features a lockable bill box for high-security with acceptance rate up to 96% or greater.

Specifications



Acceptance Rate

96% or greater



Bill Insertion

Four-way



Bill Width Accepted

62~66 mm/2.44~2.6 inches



Acceptance Speed

Approx. 3 sec. to cash box



Capacity

Approx. 200 notes cashbox
Approx. 500 notes cashbox
Approx. 1000 notes cashbox



Interface

TAO-A I: Pulse, ICT Protocol, NISR,
5V ENABLE, Single Price.
TAO-V I: Pulse, ICT Protocol, MDB.



Power Source

TAO-A I: 12V DC(10.8V~13.2V DC)
117V AC(105.3V~128.7V AC)
TAO-V I: 12V DC(10.8V~13.2V DC)
24V AC(21.6V~26.4V AC)
24V/34V DC(20V~42.5V DC)



Recommended Applications

Vending, Gaming, Kiosk, Amusement



Power Consumption

TAO-A I: 12V DC- Standby : 0.3A, 4W
Operation: 0.9A, 11W
Maximum: 2.6A, 32W
117V AC- Standby : 0.04A, 5W
Operation: 0.12A, 15W
Maximum: 0.4A, 47W
TAO-V I: 12V DC- Standby : 0.3A, 4W
Operation: 0.8A, 10W
Maximum: 2.5A, 30W
24V AC- Standby : 0.2A, 5W
Operation: 0.5A, 12W
Maximum: 1.5A, 36W
24V/34V DC- Standby : 0.15A, 6W
Operation: 0.4A, 14W
Maximum: 1.35A, 46W



Dimension

TAO-A/V I-P2:
(W)106.3 x (D)174.9 x (H)247.5mm/
(W) 4.19 x (D)6.89 x (H)9.74 inches
TAO-A/V I-P5:
(W)106.3 x (D)219.9 x (H)247.5mm/
(W)4.19 x (D)8.66 x (H)9.74 inches
TAO-A/V I-P10:
(W)106.3 x (D)318.9 x (H)253.9mm/
(W)4.19 x (D)12.56 x (H)10 inches



Weight

TAO-A/V I-P2 : Approx. 1.22 kg/ 2.68 lbs
TAO-A/V I-P5 : Approx. 1.35 kg/ 2.97 lbs
TAO-A/V I-P10: Approx. 1.72 kg/ 3.79 lbs



Environmental

Operating Temperature: 0°C/ 32°F~55°C/ 131°F
Storage Temperature: -30°C/ -22°F~70°C/ 158°F
Humidity: 30%~85% RH (no condensation)

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw