

TAO-V-MUP4(MXP2+USD2)

TAO-V Option Switch Settings: 1(Pulse/MDB)

**Supported bill MXP 20, 50
USD 1, 5 4bills.**

TAO-V dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject USD 1	ON											
★ Accept USD 1	OFF											
★ Reject MXP 20		ON										
★ Accept MXP 20		OFF										
★ Reject MXP 50			ON									
★ Accept MXP 50			OFF									
★ Reject USD 5				ON								
★ Accept USD 5				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ Reserved						ON						
★ Reserved						OFF						
Pulse Mode	Other Mode											
★ Harness Disable	BA stops working when fishing					ON						
★ Harness Enable	Normal					OFF						
★ Inhibit Active High							ON					
★ Inhibit Active Low							OFF					
★ 1 pulse / MXP 10 & USD 1								OFF	OFF			
★ 2 pulses / MXP 10 & USD 1								ON	OFF			
★ 5 pulses / MXP 10 & USD 1								OFF	ON			
★ 10 pulses / MXP 10 & USD 1								ON	ON			
★ Interface Timing Conversion	50ms LO / 50ms HI									OFF	OFF	
	60ms LO / 300ms HI									ON	OFF	
	30ms LO / 50ms HI									OFF	ON	
	150ms LO / 150ms HI									ON	ON	

★ Default setting

★★ Use 2nd dip switch of the internal dip-switch to change different interface protocol.

Note :1. For Accepting US Dollars Exchange Rate on USD to MXP is 1:18 for MDB Mode

TAO-V-MUP4(MXP2+USD2)(Pulse/MDB)

Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	USD 1	USD 1
BV2	MXP 20	MXP 20
BV3	MXP 50	MXP 50
BV4	USD 5	USD 5